



VERDECON B.V.
 CLEANING SOLUTIONS & TOOLS
 9é LINIESTRAAT 19G
 3200 AARSCHOT

MH 4M – Warmwaterhogedrukreinigers – medium klasse



Performance, long life-time and ergonomics

- High efficiency 4 pole motors
- EcoPower boiler with EcoMode function
- Brass pump head
- Flow or Pressure activated unloader system
- Innovative design with 4 big wheels
- Easy to transport, can even be pushed/pulled across uneven surfaces
- Diesel oil tank with level sight
- As standard delivered with 10l external detergent tank (A) and space for an extra tank (B)
- Low fuel warning system
- Onboard diagnostics function

The MH 4M series takes mid-range hot water high pressure washers to a new level, meeting the latest productivity demands in the market. The MH 4M is equipped with our industrial NAS pump with 3 ceramic pistons and a high efficiency 4 pole motor. And the flow activated control system improves user comfort and handling as well as overall machine reliability.



TECHNISCHE GEVEGENS	MH 4M-130/720 FA	MH 4M-180/860 FA	MH 4M-180/860 FAL	MH 4M-200/960 FA	MH 4M-200/960 FA EXPT	MH 4M-200/960 FA NO
Aanbevolen gem. gebruiksuren per dag	5	5	5	5	5	5
Pompdruk (bar/MPa)	130/13	180/18	180/18	200/20	200/20	200/20
Reinigingsimpact (kg/force)	3	4.3	4.3	5.1	5.1	5.1
Watercapaciteit Qmax-Qiec (l/u)	720/660	860/790	860/790	960/890	960/890	960/890
Pomp (tpm)	1450	1450	1450	1450	1450	1450
Watertemperatuur (water/stoom) (°C)	90/150	90/150	90	90/150	90/150	90/150
Watertoevoertemperatuur, max. (°C)	40	40	40	40	40	40
Brandstofverbruik (ΔT=45 °C) (kg/u)	2.9	3.5	3.5	3.9	3.9	3.9
Brandstoftank (l)	15	15	15	15	15	15
Langte x breedte x hoogte (mm)	1010x700x1016	1010x700x1016	1010x700x1016	1010x700x1016	1010x700x1016	1010x700x1016
Gewicht (kg)	141	133	133	142	142	144
Stroomverbruik (kW)	3.6	5.9	5.9	7.2	7.2	7.2
Elektrische aansluitwaarden (V~/Hz/A)	230/1/50/16	400/3/50/10	400/3/50/10	400/3/50/12	220/440/3/60/21/12	230/400/3/50/21/12
Reinigingsmiddelentank (l)	A: 10 + B:	A: 10 + B:	B: 10	A: 10 + B:	A: 10 + B:	A: 10 + B:
Keramische plunjers	3	3	3	3	3	3
Elektrokabel (m)	5	5	5	5	5	5
Sproeiërgrootte	.0435	.0435	.0435	.0475	.0475	.0475
KENMERKEN						
• Waarschuwing voor laag oliepeil	•	•		•	•	•
• Service indicator	•	•	•	•	•	•
• Vertraagde automatische start/stop	•	•		•	•	•
• 2 x reinigingsmiddel injecteur	•	•		•	•	•
• Watertoevoer instelling	•	•		•	•	•
• Oliepeilglas extern	•	•	•	•	•	•
STANDAARD TOEBEHOREN						
Snelkoppingsset ERGO aansluiting	101119496	101119496	101119496	101119496	101119496	101119496
Slangnozzle	61369	61369	61369	61369	61369	61369
Terugslagklep Gardena koppeling	106411177	106411177		106411177	106411177	106411177
Hogedruk slang 5/16 inch 10 m	101405770	101405770	101405770	101405770	101405770	101405770
ERGO 2000 st. + anti-draaikoppeling	106403122	106403122	106403122	106403122	106403122	106403122
TornadoPlus 1000 gebogen				106403011	106403011	106403011
Universal Plus 940	106403036	106403036	106403036			
TornadoPlus nozzle 0425 1/8 inch	101119739	101119739	101119739			
TornadoPlus nozzle 0475 1/8 inch				301150005	301150005	301150005
Filter 50µ	107144272	107144272		107144272	107144272	107144272
ARTIKELNUMMER	107146915	107146917	107146916	107146920	107146924	107146921
BRUTOPRIJS EXCL. BTW €	4.191,00	4.246,00	3.970,00	4.521,00	op aanvraag	4.963,00