



VERDECON B.V.
 CLEANING SOLUTIONS & TOOLS
 9é LINIESTRAAT 19G
 3200 AARSCHOT

SH SOLAR G – Stationary hot water

Gas powered stationary hot water high pressure washers

- Expandable control technology with PLC and special options
- Automatic diagnosis and fault finding
- Efficient gas heating systems
- Galvanised steel frame and cabinet
- Reduced running and service costs
- Compact and easy to install

Gas powered stationary heating for maximum efficiency in the automotive, industrial sectors or other sites possessing a gas supply line, avoiding need to provide diesel fuel supply.



| TECHNICAL DATA | SH SOLAR 5M-150/1020 G | SH SOLAR 7P-170/1200 G |
|---|------------------------|------------------------|
| Recommended avg. hours of use per day | 5 | 7 |
| Pump pressure (bar/MPa) | 150/15 | 170/17 |
| Cleaning impact (kg/force) | 4.5 | 5.8 |
| Water flow Qmax/Qiec (l/h) | 1020/900 | 1200/1110 |
| Max. temperature (°C) | 99 | 99 |
| Max. inlet temperature (°C) | 30 | 30 |
| Water temperature, ΔT at full flow (°C) | 85 | 85 |
| Length x width x height (mm) | 700x900x1100 | 700x900x1100 |
| Weight (kg) | 186 | 214 |
| Nozzle size | .0550 | .0680 |
| FEATURES | | |
| Automatic start/stop | • | • |
| 1450 rpm motor | • | • |
| Galvanised steel frame | • | • |
| PLC and expandable control electronics | • | • |
| Gas burner and coil | • | • |
| Auto fault finding | • | • |
| Water brake tank | • | • |
| ITEM NO. | 107370450 | 107370470 |